

Item Code: IJTG20055

PRINTeS™ - Acquous inkjet 200 Glossy – Coated DuPont™ Tyvek®

Introduction

Acquous inkjet printing media made up of white spunbonded high density polyethylene media, with exceptionally high tear resistance. High dimensional stability, chemically and biologically inert. Compatible to both mechanical and chemical recycling.

Printing

- Suitable for any plotters like HP Page Wide or HP, Epson and Canon Printers
- Prints well on Mimaki, Epson and other Inkjet label printers

Features

- Weather and tear-resistant media for long lasting prints
- Water resistant* when printed with Pigment based inks
- Good Scratch & Rub resistance
- Excellent flexural strength – good for places where folding is needed (viz Architectural Drawings)
- Offers excellent print quality when selected with respective Printer specified media – for example in an Epson desktop printer, please use the media option as “Epson Matte” and in case of HP Desktop printer, please use the option of “HP Premium Matte” media.
- While printing on HP Page Wide printers, please select Settings > Media > Banners > DuPont™ Tyvek® Banner


Applications

- Architectural / Archival / Engineering / Wiring Drawings
- Building and Site Plans
- Underwater Maps, Weather Resistant Prints
- Face stock for Inkjet Printable Labels

Technical Specifications

Basis Weight :	72 GSM
Caliper :	200 micron (+/-10%)
Tensile :	108 / 124 (MD/CD) N
Tear (Elmendorf) :	4.7 / 5.0 (MD/CD) N
Opacity :	98%
Flexural Strength:	20,000 cycles
Available Sizes :	595 mm & 895 mm
Core Sizes :	2" & 3"
Roll Length :	75 Mts. (3" Core)


* Slight Color Bleed can be expected in some desktop printers in Black & Cyan.
Allow 48 Hrs.curing for higher water resistance



Architectural Drawings



Building and Site Plans



Underwater Maps



Inkjet Printable Labels

DuPont™ Tyvek® are trademarks or registered trademarks of E. I. du Pont de Nemours and Company or its affiliates. | PRINTeS™ is a registered trade mark of TES Techno Coats Pvt Ltd

Important Note: All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and following is made in lieu of all warranties of merchantability and fitness for the purpose. Sellers and manufacturers on obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine suitability of the product for intended use, and user assumes all risk and liability whatsoever in connection therewith. In our endeavor to continually improve our products, all specifications are subject to change without any prior notice or intimation.

Marketing Office:

Rahul Mansion, Plot Nos. 128 & 129,
H. No. 5-5-35/29, Prasanthnagar I.E. Kukatpally,
Hyderabad, Telangana - 500 072, India.
T : +91 40 4007 1748, 4221 5498
Email : info@tespackaging.com

Factory Address:

Survey No. 42/AA2, Erdhanoor,
Sangareddy Mandal, Hyderabad,
Telangana - 502319, India.
T : +91 40 4007 1748, 4221 5498
Email : info@testtechnocoats.com

www.testtechnocoats.com